

ANALOG TIMERS

OZ - ST3P SERIES	TIME RANGE	VOLTAGE	
OZ-ST3P-AA	0.5s / 5s / 30s / 3min	12V DC / 24V AC / 24V DC / 110V AC / 220V AC / 415V AC	
OZ-ST3P-AB	1s / 10s / 60s / 6min		
OZ-ST3P-AC	5s / 50s / 5min / 30min		
OZ-ST3P-AD	10s / 100s / 10min / 60min		
OZ-ST3P-AE	60s / 10min / 60min / 6h		
OZ-ST3P-AF	2min / 20min / 2h / 12h		
OZ-ST3P-AG	4min / 40min / 4h / 24h		
OZ-ST3P-F (Off Delay)	1s / 5s / 10s / 30s / 60s / 3min	110V AC / 220V AC	
OZ-ST3P-Y [30sec] (STAR-DELTA)	30s		
OZ-ST3P-Y [60sec] (STAR-DELTA)	60s		
OZ-ST3P-R [30sec/30min]	30s / 30m		

OZ - AH3 SERIES [220V AC]	TIME RANGE	VOLTAGE	
OZ-AH3-NA	1s / 10s / 1m / 10m	220V AC	
OZ-AH3-NB	3s / 30s / 3m / 30m		
OZ-AH3-NC	6s / 60s / 6m / 60m		
OZ-AH3-ND	1m / 10m / 1h / 10h		

OZ - AH3 SERIES [220V AC]	TIME RANGE	VOLTAGE	
OZ-AH3-1	1s / 3s / 6s / 10s / 30s / 60s	220V AC	
OZ-AH3-2			
OZ-AH3-3			

OZ - H3BA SERIES	TIME RANGE	VOLTAGE	
OZ-H3BA-8 [8 Pin]	0.5s to 100h	24 - 240V AC/DC	
OZ-H3BA-11 [11 Pin]			

OZ - H3CRA SERIES	TIME RANGE	VOLTAGE	
OZ - H3CRA - 8 [8 Pin] OZ - H3CRA - 11 [11 Pin]	1.2s to 300h	24 - 240V AC/DC	
OZ - AH2Y SERIES [220V AC]	TIME RANGE	VOLTAGE	
OZ - AH2Y OZ - AH2 - YA OZ - AH2 - YB OZ - AH2 - YC	3s / 10s / 30s / 60s 1s to 10m 3s to 30m 6s to 60m	220V AC	
OZ - H3Y SERIES	TIME RANGE	VOLTAGE	
OZ - H3Y2 [8 Pin] OZ - H3Y4 [14 Pin]	1s / 5s / 6s / 10s / 30s / 60s / 3m / 5m / 10m / 30m	220V AC / 110V AC / 24 V DC / 24V AC / 12V DC	

OZH – 189 (24hr/Street Light Timer)



PARAMETERS

SUPPLY VOLTAGE	_____	240 VAC
FREQUENCY	_____	50/60 Hz
POWER CONSUMPTION (MAX.)	_____	2 VA
ACCURACY	_____	±1.5 S/DAY AT 20°C
RELAY OUTPUT	_____	1C/O
CONTACT RATING	RESISTIVE	16A @ 250 VAC, 0.25A @220 VDC
	INDUCTIVE (cos = 0.6)	8A @ 250 VAC, 0.1A @ 220 VDC
	INCANDESCENT LAMP	1350 W
SHORTEST SWITCHING TIME	DAILY	15min
	WEEKLY	2h
POWER RESERVE	_____	150h
MEMORY LOCATIONS	_____	N.A
STORAGE TEMPERATURE	_____	-20°C TO +55°C
MANUAL OVER-RIDE	_____	PROVIDED
MOUNTING	_____	FLUSH,BASE / DIN rail
WEIGHT (UNPACKED)	_____	185 g

DIGITAL TIMERS

DIGITAL TIMERS	TIME RANGE	VOLTAGE	
OZ - DH48S - ZZ [8 Pin] OZ - DH48S - ZZ [11 Pin]	0.1s to 99h99m	12V DC / 24V DC / 220V AC	
OZ - DH48S - S [8 Pin]	0.1s to 99h	220V AC	
OZ - DH48S - S [8 Pin] OZ - DH48S - S [11 Pin]	0.1s to 99h	220V AC	

ASY SERIES	TIME RANGE	VOLTAGE	
ASY - 2D - 220V AC	9.9s / 99s / 9.9min / 99min	220V AC	
ASY - 3D - 220V AC	99.9s / 999s / 99.9m / 999m	220V AC	
ASY - 2SM - 220V AC (0.1s to 99m)	0.1s to 99m	220V AC	
ASY - 3SM - 220V AC (0.1s to 999m)	0.1s to 999m	220V AC	

AHC 15-A


LOAD CAPACITY	16A 250VAC (OHMIC LOAD COS ϕ = 1)
ON/OFF OPERATION	10 ON & 8 OFF
MINIMUM INTERVAL	1 MINUTE
DISPLAY	LCD
BATTERY BACKUP	150H
POWER CONSUMPTION	5VA


OZ - TR612

OZ - KG10M

'TM' TYPE TIMERS	AMPERE	VOLTAGE	
------------------	--------	---------	--

4 Pin	30 Amp (external battery)	220V AC
5 Pin	30 Amp (external battery)	220V AC

